

RAY R6B-O

Cloud-managed 4x4:4 Wi-Fi 6
access point

Maximum aggregated speed of 3.6 Gbps
Built for demanding environments



R6B-O



HIGHLIGHTS

- Rugged, IP67 rated sustains in extreme weather conditions.
- Wi-Fi 6 driven High-Performance.
- Bundled High-Power Omnidirectional Antennae & Mounting Kit.
- Pocket friendly, helps in lowering the TCO.
- Radio Chains and Streams UL/DL MU-MIMO, 4x4:4 (5 GHz), 4x4:4 (2.4GHz)
- 802.11ax up to 3.6 Gbps dual aggregate frame rate.
- One Gigabit Ethernet port, 802.3af PoE compatible.
- Dynamic Segmentation and policy-enforcement firewalls.



SPECIFICATIONS	R6B-O
AP Type	Rugged Outdoor Ultra High-Performance Access Point
MIMO	4x4 SU-MIMO 4x4 MU-MIMO
Max Aggregate frame rate	Max aggregate frame rate: Up to 3.6 Gbps › 2.4GHz: 1147 Mbps › 5GHz: 2402 Mbps
LAN Ports	1 x 10/100/1000/2500M BASE-T Ethernet (RJ45) PoE
Wi-fi 6	High-Density Outdoor Use Case Ultra-High Performance

Note: Antenna will be delivered with the Product.

RAY ONE



RAY Essential



RAY Premium

Services



Edge
Gateway



Switch



Wi-Fi



Sase

Products



Orchestration



Integration



Automation

Centralized
Management



SD-Wan



Firewall



HSIA



Multiwan

Security driven
Networking



Linux
Networking



Multiple
Interfaces



Hardware

Ray OS



Appliance



Virtual

Ray One is a Next Generation Solution for the challenges of today.

Ray One powers Unified Networking and Security across Networks, endpoints, and clouds in a purpose-built cloud-delivered infrastructure that scales.

It employs concepts of convergence to consolidate multiple point products including Cloud SWG, NG CASB, FWaaS, SD-WAN and ADEM, into a single integrated service provide comprehensive cybersecurity protection for all users, devices, and applications and across all network edges. It reduces network and security complexity while increasing organizational agility and ensuring compliance, emphasizes interoperability as well as analytics, intelligence, centralized management, and automation, and integrates with a broad ecosystem of technologies and vendors.

What sets One Apart and distinguished is that it has a network wide visibility with a single pane of glass dashboard and control. Security comes in seamless with automatic firmware updates as well as automatic reporting. One has a unique feature of Self-provisioning for rapid deployment. One being cloud based consists of Cloud based RF Planning. Built-In spectrum analysis as well as Dual- Concurrent radios with band steering come in as features that set apart RF Planning with ONE.

As you will see further all features described in detail for Ray One, we would still like to highlight a couple of features that makes it Secured.

Ray One powered Edge Gateways, Switches and Wireless (Wi-Fi) devices are available to deploy on any network edge.



FEATURES

Adaption for changing business dynamics to address modern requirements funnel downs to Network Architecture. Today Ray is being managed and delivered through cloud which enhances features like scalability, speed and flexibility. Enterprises with

Ray are able to leverage powerful automated, zero touch, delivering on demand and a proactive business approach. One Features help the enterprise to make intelligent decisions that adhere business goals and objectives.



Secure SD-WAN

Ray One powers extremely Secure & Advanced SD-WAN with top-tier features like Application Identification & Control, Application-aware traffic control, and Performance Optimization Helping you enable remote working through a secure Access Client & ZTNA. Automatically optimize routing and rerouting of traffic based on WAN Link performance (latency, jitter, loss) in real time with zero impact.

Advance Networking

Ray One powers the most advanced and Secure enterprise-grade networking technology available for NAT, routing, and bridging across all the Edges even empowering Hybrid workforce. It includes Advance routing, Dual Stack Support, static, OSPF, BGP, and RIP with full 802.1Q VLAN support, Multicast, QOS Enablement and Traffic Classification and control amongst others.



Security

Ray One keeps the Enterprise secure even from Ransomware, Malware and even Zero Day threats through high-performance streaming deep packet inspection, next-gen IPS, web protection, DNS Filters, and app control. The powerful Enterprise policies help create Trust Zones in the Network. Ray One enables fast, coordinated detection and enforcement across the entire attack surface to counter the latest known and unknown threats in real time. The threat research is unified data sets feeding from networks, endpoints, and clouds, rich independent research, and comprehensive industry collaboration.

FEATURES

Cloud Architecture

Ray Always One Cloud is Microservices bring unparalleled agility, scale, resiliency. Ray makes it easy to add or remove new features by leveraging a microservices cloud architecture. New enhancements and bug fixes are delivered almost weekly without network disruption. Services scale up or down elastically when they're needed, eliminating the cost and complexity of monolithic hardware.



HSIA (Captive Portal)

Ray One powers 9 kinds of Captive Portal and Guest onboarding flows with advance features like WYSIWYG, Advertisement Server, Survey engine, Payment Gateway along, Multi Language support etc. The Wi-Fi Monetization makes Ray revenue centre for the enterprise. Guest Analytics helps to make data driven business decisions that help growth and revenue.

WAN Suite

Ray One powered Link Bonding taps into the bandwidth of multiple WAN sources to provide a single bonded data-pipe that enables higher speed and resiliency whilst being economical, fast, and easily configurable to suit any networking environment.



Dimensions & Interfaces

AP Name	
R6B-O	
Wi-Fi	
Wi-Fi Standards	802.11 ax/ac/b/g/n
AP Type	Outdoor, Wi-Fi 6 dual radio, 5 GHz 4x4 MIMO and 2.4 GHz 4x4 MIMO
MIMO	› 4x4 SU-MIMO › 4x4 MU-MIMO
802.11ax, 802.11ac Wave 2 and 802.11n Capabilities	› DL-OFDMA, UL-OFDMA, TWT support, BSS Coloring › 4 x 4 multiple input, multiple output (MIMO) with four spatial streams › SU-MIMO, UL MU-MIMO and DL MU-MIMO support › Maximal ratio combining (MRC) & beamforming › 20 and 40 MHz channels (802.11n); 20, 40, and 80 MHz channels (802.11ac Wave 2); 20, 40 and 80 MHz channels (802.11ax) › Up to 1024-QAM on both 2.4 GHz & 5 GHz bands › Packet aggregation: A-MPDU, A-MSDU
Radio 2.4GHz	Four spatial stream Single User (SU) MIMO for up to 1,147 Mbps wireless data rate with individual 4SS HE40 802.11ax client devices or with two 2SS HE40 802.11ax MU-MIMO capable client devices simultaneously
Radio 5GHz	Four spatial stream Single User (SU) MIMO for up to 2,402 Mbps wireless data rate with individual 4SS HE80 (or 2SS HE160) 802.11ax client devices, or with four 1SS or two 2SS HE80 802.11ax MU-MIMO capable client devices simultaneously
Max aggregate frame rate	› Max aggregate frame rate: Up to 3.6 Gbps › 2.4 GHz: 1,147 Mbps › 5 GHz: 2,402 Mbps
Supported Data Rates (Mbps)	› 802.11b: 1, 2, 5.5, 11 › 802.11a/g: 6, 9, 12, 18, 24, 36, 48, 54 › 802.11n: 6.5 to 600 (MCS0 to MCS31, HT20 to HT40), 800 with 256-QAM › 802.11ac: 6.5 to 1,733 (MCS0 to MCS9, NSS = 1 to 4, VHT20 to VHT160), 2,166 with 1024-QAM › 802.11ax (2.4GHz): 3.6 to 1,147 (MCS0 to MCS11, NSS = 1 to 4, HE20 to HE40) › 802.11ax (5GHz): 3.6 to 2,402 (MCS0 to MCS11, NSS = 1 to 4, HE20 to HE160)
Supported frequency bands	› Software enabled country-specific restrictions apply › 2.412-2.484 GHz › 5.150-5.250 GHz (UNII-1) › 5.250-5.350 GHz (UNII-2) › 5.470-5.600, 5.660-5.725 GHz (UNII-2e) › 5.725 -5.825 GHz (UNII-3)

Supported Channels	Available channels dependent on configured regulatory domain › 2.4 GHz: 1-13 › 5 GHz: 36-64, 100-144, 149-165 Dynamic frequency selection (DFS) optimizes the use of available RF spectrum
Supported Radio Technologies	› 802.11b: Direct-sequence spread-spectrum (DSSS) › 802.11a/g/n/ac: Orthogonal frequency-division multiplexing (OFDM) › 802.11ax: Orthogonal frequency-division multiple access (OFDMA) with up to 37 resource units (for an 80MHz channel)
Supported Modulation Types	› 802.11b: BPSK, QPSK, CCK › 802.11a/g/n: BPSK, QPSK, 16-QAM, 64-QAM › 802.11ac: BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM › 802.11ax: BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM, 1024-QAM
Radio Chains and Spatial Streams	› 4x4:4 streams SU/MU MIMO 5 GHz › 4x4:4 streams SU/MU MIMO 2.4 GHz
Channelization/PHY Types	› 802.11n high-throughput (HT) support: HT20/40 › 802.11ac very high throughput (VHT) support: VHT20/40/80/160 › 802.11ax high efficiency (HE) support: HE20/40/80/160
Wireless Authentication	› WEP, WPA, WPA2-PSK, WPA3 - Personal, WPA3 - Enterprise, WPA3 - Enhanced Open (OWE) › Dynamic PSK › EAP-TLS, EAP-TTLS, EAP-MSCHAPv2, EAP-SIM › IEEE 802.1X based Authentications › Captive Portal Based Authentications
Advance Features	› Advanced Cellular Coexistence (ACC) minimizes interference from cellular networks › Maximum ratio combining (MRC) for improved receiver performance › Cyclic delay/shift diversity (CDD/CSD) to enable the use of multiple transmit antennas › Short guard interval for 20-MHz, 40-MHz and 80-MHz › Space-time block coding (STBC) for increased range and improved reception › Low-density parity check (LDPC) for high efficiency error correction and increased throughput › Transmit beam-forming (TxBF) for increased signal reliability and range

Beamforming	Transmit Beamforming and Maximal Ratio Combining
Band Steering	Band steering for 5 GHz clients to connect over 5 GHz Radio to provide better load balancing among 2.4 GHz and 5 GHz Radios.
Beaconing	- Transmit Only - Transmit/Receive (Attached Devices) - Transmit/Receive (Unattached Devices)
Roaming/Mobility	- Support for IEEE 802.11r or Fast BSS Transition (FT) - Centralized Layer 3 roaming - Seamless Roaming for Captive Portal users

RADIO RESOURCE MANAGEMENT

RF Management	Dynamic RF management to detect and mitigate interference from Wi-Fi
Wi-Fi Channel Management	Automatic Channel Selection by Intelligent Radio Resource Management (iRRM)
Wi-Fi Radio Power Management	Optimum Power management by Intelligent Radio Resource Management (iRRM)
Wi-Fi QOS	Self-healing (on detection of RF interference or loss of RF coverage).

ANTENNA

Antenna (Included in Box)	2.4GHz omni-directional External N Type antennas with 6 dBi peak gain 5GHz omni-directional External N Type antennas with 6 dBi peak gain
----------------------------------	--

WIRELESS SECURITY

Wireless Security	- Real-time WIPS/WIDS with instant alerting - Classify Types of Rogue AP - WLAN-Spoofing - Same-Network - MAC-spoofing
--------------------------	--

MESH

SON based Mesh	- Self-configuring - Self-defending - Self-healing - Self-managing
-----------------------	---

Wi-Fi OFFLOAD

- Passpoint Wi-Fi (Release 2) (Hotspot 2.0) for Seamless cellular-to-Wi-Fi - Access Network Discovery and Selection Function (ANDSF) Integration

RADIO MANAGEMENT

Antenna Optimization	Maximal Ratio Combining (MRC)
Client Density Management	Client Load Balancing distribute clients to the least loaded 802.11 channel and AP
Airtime Fairness	Enhance general client performance

POWER

Peak Transmit Power (Tx port/chain + Combining gain)	- Limited by local regulatory requirements 2.4 GHz band: +23 dBm per chain, +26 dBm aggregate 5 GHz band: +23 dBm per chain, +26 dBm aggregate - Note: conducted transmit power levels exclude antenna gain.
Transmit power	Configurable in increments of 0.5 dBm
Maximum EIRP (2.4 GHz band)	- Limited by local regulatory requirements 2.4 GHz band: 565: 29.2 dBm EIRP 567: 33 dBm EIRP
Maximum EIRP (5 GHz band:)	- Limited by local regulatory requirements 5 GHz band: 565: 31.4 dBm EIRP 567: 32.7 dBm EIRP

NMS INTEGRATION

SNMP support

PERFORMANCE

Maximum number of associated client devices	Up to 512 clients per AP
Maximum number of BSSIDs	16 BSSIDs per radio - Up to 31 per AP

NETWORKING

IP	IPv4, IPv6, dual stack
VLAN	802.1Q (1 per BSSID or dynamic per user based on RADIUS) - VLAN Pooling - Port-based
802.1x	Authenticator & Supplicant
Tunnel	- L2TP - GRE/EoGRE - Openvpn - L2TP/IPSEC
Policy Management Tools	- Application Recognition and Control - Access Control Lists - Device Fingerprinting - Rate Limiting - Integrated Layer 7 firewall with mobile device policy management - Flexible guest access with device isolation

Quality of Service	› WMM Access Categories with DSCP and 802.1p support › QoS-based scheduling › Directed Multicast › L2/L3/L4 ACLs
Modes	› Gateway Mode › Bridge & Firewall › Bridge No Firewall
External Authentication	› Authentication via Radius › Authentication via LDAP › Authentication via Single Sign-On (SSO) › Authentication via Active Directory (AD)
Radius	› Radius Option 82 Support
Tunnel	› L2TP › GRE/EoGRE › Openvpn › L2TP/IPSEC › PPTP › Wireguard/SSL
L3 Features	Routing Protocols: › Static unicast routes › Equal cost multipath routing (ECMP) › RIP v1/v2 › OSPF › BGP4+ › VRRP › Generic routing encapsulation (GRE) › Standard 802.1d Spanning Tree Protocol › Network Address Translation (NAT) › Dynamic Host Configuration Protocol (DHCP) › server, relay, and client › Access control lists (ACLs) › IPv4 and IPv6 Multicast

NETWORK SECURITY

- › Integrated Layer 7 firewall with mobile device policy management
- › Flexible guest access with device isolation
- › VLAN tagging (802.1q) and tunneling with IPsec VPN
- › Secure Boot, runtime defences/image signing/integrity verification, and hardware authenticity.
- › IP filtering policies or ACL
- › Device Profiling & VLAN mapping
- › L2 Isolation, ARP Blocking
- › DDoS Detection

ENTERPRISE POLICY

Enterprise Policies (Applicable Per User/Group/SSID)	› Time Policy to Control the Access Time › Speed Policy to Control Upload/Download Bandwidth › Device Policy to control Device Type › Quota Policy to control Time or Volume Usage › Concurrency Policy to control simultaneous user login › Application Policy to control L7 Policy › Web Categorization Policy to control browsing by Category › DNS Filter Policy to filter DNS requests
---	--

QUALITY OF SERVICE (QOS)

- › Advanced Power Save (U-APSD)
- › WMM Access Categories with DSCP and 802.1p support
- › Layer 7 application traffic identification, prioritization & shaping Per SSID/Group/User
- › QoS configuration for applications based on categories.
- › 802.11e WMM Support

GUEST CAPTIVE PORTAL

Guest Captive Portal Authentication Modes	› Click To Login › Voucher › Username & Password › SMS OTP › Email OTP › Custom Survey › Social Media › Advertisement › Payment Gateway
Survey Engine	› Create Custom Survey with the below Questions › Short Answer › Long Answer › Email ID › Phone Number › Star Rating › Smiley Rating › Dropdown › Radio Button › Multi Select
Advertisement Engine	› Display Picture or Video Advertisements Per Venue › Display Statistics, Clicks, Views, Revenue generated per Venue/Advertisement
PMS Integration	Oracle Opera PMS and Fidelio Suite8 PMS (IFC Part Number 5009-313)

FIRMWARE

- › Flash Security Updates (No Reboot Required)
- › Cloud Managed Firmware Updates

PHYSICAL INTERFACES

Ethernet (WAN)	1x 100/1000/2.5G BASE-T Ethernet (RJ45) - Power over Ethernet (802.3af/at) with Category 5/5e/6 cable PD. - LLDP - Auto-sensing link speed and MDI/MDX 802.3az Energy Efficient Ethernet (EEE)
Reset Button	Reset to the factory default settings

DIMENSIONS

Physical Size	- L=295 - B=231 - H=80
Weight	3.78 kg

MOUNTING

- Mounts to walls and horizontal, vertical, and angled poles
- All standard mounting hardware included

ENVIRONMENTAL

Operating temperature	-40° C to +55° C (-40° F to +140° F) with full solar loading
Humidity	5%~95% non-condensing Internal Rated for operation in all weather conditions
Storage Temperature	-40° C to +70° C (-40° F to +158° F)
Storage Humidity	5%~95% non-condensing Internal
Operating Altitude	3,000 m
Water and Dust	IP66/67 Environmental rating
Wind Survival	Up to 165 Mph
Shock and Vibration	ETSI 300-19-2-4

POWER

Maximum (worst-case) power consumption:	24W
Maximum (worst case) power consumption in idle mode:	6.1W
Maximum (worst case) power consumption in deep-sleep mode:	3.3W Power sources sold separately
802.3at PoE+	18.71W
Power over Ethernet (PoE+):	802.3at-compliant

SURGE PROTECTION

Common Mode Surge Protection	6KV
Differential Mode Surge Protection	2KV

RELIABILITY

Mean Time Between Failure (MTBF): 75,000 hrs at +25°C operating temperature

CONTROLLER

Public Cloud	Ray ONE hosted on Public Cloud
Private Cloud	Ray ONE hosted on Private Cloud/Data-center

WARRANTY

As per the purchased SKU

BOX CONTENTS

- Standard Mounting Kit
- Ethernet Cable
- Quick Start Guide



SPECIFICATIONS

2.4GHZ RECEIVE SENSITIVITY (dBm)

HT20		HT40		VHT20		VHT40	
MCS0	MCS7	MCS0	MCS7	MCS0	MCS11	MCS0	MCS11
-92	-72dBm	-90dBm	-71dBm	-93dBm	-63dBm	-91dBm	-60dBm

5GHZ RECEIVE SENSITIVITY (dBm)

HT20		HT40			
MCS0	MCS7	MCS0	MCS7		
-93dBm	-75dBm	-91dBm	-72dBm		
VHT20		VHT40		VHT80	
MCS0	MCS11	MCS0	MCS11	MCS0	MCS9
-93dBm	-74dBm	-91dBm	-72dBm	-88dBm	-62dBm
HE20		HE40		HE80	
MCS0	MCS11	MCS0	MCS11	MCS0	MCS11
-93dBm	-63dBm	-90dBm	-60dBm	-87dBm	-56dBm

2.4 GHZ RF Power

MCS0	HT20	23±1dBm
MCS7	HT20	22±1dBm
MCS0	HT40	22±1dBm
MCS7	HT40	21±1dBm
MCS0	HE20	21±1dBm
MCS11	HE20	20±1dBm
MCS0	HE40	20±1dBm
MCS11	HE40	19±1dBm

5 GHZ RF Power

MCS0	HT20	23±1dBm
MCS7	HT20	22±1dBm
MCS0	HT40	22±1dBm
MCS7	HT40	21±1dBm
MCS0	VHT20	22±1dBm
MCS9	VHT20	21±1dBm
MCS0	VHT40	22±1dBm
MCS9	VHT40	20±1dBm
MCS0	VHT80	20±1dBm
MCS9	VHT80	19±1dBm
MCS0	HE20	21±1dBm
MCS11	HE20	20±1dBm
MCS0	HE40	20±1dBm
MCS11	HE40	19±1dBm
MCS0	HE80	19±1dBm
MCS11	HE80	18±1dBm

SUBSCRIPTIONS

ESSENTIAL	PROTECT
Cloud Subscription	Cloud Subscription
Support (8 x 5)	Support (8 x 5)
L3 Networking	L3 Networking
Advance Wireless & RRM*	Advance Wireless & RRM*
WAN Suite	WAN Suite
	Network & Web Protection
	Captive Portal
12 Months (Renewal required)	12 Months (Renewal required)
36 Months (Renewal required)	36 Months (Renewal required)
60 Months (Essential Lifetime)	60 Months (Essential Lifetime)

***Note:** Available only for Wi-Fi enabled devices.

HARDWARE WARRANTY

Essential Hardware Warranty	Premium Hardware Warranty
Available for 1, 3 & 5 years	Available for 1,3 & 5 Years
Return & Replace Warranty	Advance Replacement with NBD Shipping

SOFTWARE SUPPORT

Essential Software Support	Premium Software Support
Available for 1, 3 & 5 years	Available for 1,3 & 5 Years
Support time 8*5	Support time 24*7
Email Support	Email Support
Web Support	Web Support
Chat Support	Chat Support

For More details on warranty visit: www.ray.life

BOX CONTENT

What is included in the box

1. R6B-O
2. Waterproof Kit
3. Bracket-1
4. U-Bolt Kit-2
5. Screw Set
6. Antenna



1. R6B-O



2. Waterproof Kit



3. Bracket-1



4. U-Bolt Kit-2



5. Screw Set



6. Antenna

ORDERING MECHANISM

R6B-O Hardware

SKU	Product Name	Description
RWHCC0N085	R6B-O Wi-Fi 6 Outdoor Wireless Access Point	› Wi-Fi 6 (802.11 AX) Outdoor Wireless Access Point › 3.6 Gbps › 4 x 4 MIMO › 1 x 2.5G (LAN/WAN, PoE) › 4 x Omni Directional Antenna

R6B-O Hardware Support

RWWSC0N262	R6B-O Essential Hardware Warranty (12 Months)	R6B-O 12 Months Essential Warranty Return & Replace Hardware Warranty
RWWSC6N262	R6B-O Essential Hardware Warranty (36 Months)	R6B-O 36 Months Essential Warranty Return & Replace Hardware Warranty
RWWSC8N262	R6B-O Essential Hardware Warranty (60 Months)	R6B-O 60 Months Essential Warranty Return & Replace Hardware Warranty
RWWSC0N263	R6B-O Premium Hardware Warranty (12 Months)	R6B-O 12 Months Premium Warranty Advance Replacement with NBD Ship
RWWSC6N263	R6B-O Premium Hardware Warranty (36 Months)	R6B-O 36 Months Premium Warranty Advance Replacement with NBD Ship
RWWSC8N263	R6B-O Premium Hardware Warranty (60 Months)	R6B-O 60 Months Premium Warranty Advance Replacement with NBD Ship

R6B-O Subscription Plans

RWHSC4N200	R6B-O Essential Subscription for 12 Months includes	› R6B-O Essential Subscription Includes › Cloud Subscription › Support (8 x 5) › L3 Networking › RRM › WAN Suite
RWHSC6N200	R6B-O Essential Subscription for 36 Months includes	
RWHSC8N200	R6B-O Essential Subscription for 60 Months includes	
RWHSC4N201	R6B-O Protect Subscription for 12 Months includes	› R6B-O Protect Subscription Includes › Cloud Subscription › Support (8 x 5) › L3 Networking › RRM › WAN Suite › Network & Web Protection › Captive Portal
RWHSC6N201	R6B-O Protect Subscription for 36 Months includes	
RWHSC8N201	R6B-O Protect Subscription for 60 Months includes	

USE CASES



Manufacturing Units



Warehouse



Schools



Public Wi-Fi/Hotspots



Smart Cities

CASE STUDIES

NPL Ltd.

Nairobi Plastics Ltd. manufactures plastic items and has big machines that are used to produce the same. With the increasing number of their customers & projects, the Nairobi Plastics Ltd. is working on enhancing their technologies, bringing in efficient equipment, focusing on potential emerging technologies for a value-driven product for their customers.

They are using R6B-O for the manufacturing facilities and administrative offices.

Key Takeaways

Ray's R6A – C and R6A – O, secures and connects all devices across the manufacturing unit (indoors plus outdoors).

Many sensors are used to monitor the productivity & health of each machine, where most of them are IoT devices.

Ray's Content Policy filter objectionable (inappropriate) content. E.g.: P2P, Porn, criminal sites, etc.

The Speed and Quota policies are assigned to each one, based on the role that they are playing at the manufacturing unit.

The BYOD is approved by IT admins for all visitors, guests, delivery people, etc.

The embedded security in Ray access points protects the network and filter the Malware, Ransomware and Spam.

Naivasha Safari Centre with Ray

The Naivasha Safari Centre is a retreat along the way from Nairobi to Uganda. There are almost 100, 000 vehicles, every week passing this way and spending some fun & leisure time here with their family & friends. It is widely spread in approximately 3000 m2 in different retail and gastronomic units.

Key Takeaways

They are using R6A-C and R6B-O for their indoor & outdoor areas for constant and speedy internet connection for the numerous facilities that they are offering. Ray's R6A – C and R6A – O, secures and connects all devices everywhere – indoor games areas as well as outdoor sports playing fields.

The expanse for the Naivasha Safari Centre is big and its building & activity centres are spread out in far-off places and Ray access points are placed at all ends for good connectivity.

Security is at the centre of all devices as this club has visitors on an everyday basis and they connect to the Wi-Fi with the promise of security.

Ray's Content Policy filter all the unwanted content beforehand only, so that it doesn't reach the user's device.

Privacy for everyone is maintained as this sports club has a string database of its members and visitors, which is safely stored.

Our Clients

						
						
						
						
						
						
						
						
						
						

Ray Pte. Ltd.
ray.life | sales@ray.life
Suite #09-01, 20 Collyer Quay, Singapore 049319

RAY
Secure Networking

© Copyright 2026 Ray Pte. Ltd. All Rights reserved. Ray, Ray.life and the Ray logo are trademarks of Ray Pte. Ltd. in Singapore, India and other countries. This product is protected by Singapore and international copyright and intellectual property laws. The information contained herein is subject to change without notice. The only warranties for Ray Pte. Ltd. products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Ray Pte. Ltd. shall not be liable for technical or editorial errors or omissions contained herein.